

Universal Input Type PID Electronic Temperature Controller

Fuzzy PID Technology



ETC5 PID



Intelligent Self-tuning

Fuzzy Theory Combined with Traditional PID



High Precision

Cold-end Separate Temperature Measurement



Universal Input

Multiple Signal Free Input
Full-Scale Free Setting



Alarm Assistance

1 Set of Contacts (NO or Conversion)
Upper Limit Deviation Alarm
Lower Limit Deviation Alarm
Process Value Alarm



Multiple Outputs

Default Relay/Solid-State Dual-Purpose Type



Anti-Interference

Adaptable to Various Working Environments



Adjustment

Guidance with Attached Instruction Manual




National Standard Size

Fits Standard Mounting Holes



PID Self-Tuning Adaptive Technology



Fuzzy Theory Combined with Traditional PID

Abbreviation: The fuzzy PID controller adaptively adjusts the/proportional band,integral, and derivative actions,enhancing the system with small overshoot, strong adaptability,and short adjustment time.

Universal Input

K / J / R / S / B / E / N / T / Pt100 / Cu50,etc.
Accurately covers various mainstream models



Relay/Solid-State Dual-Purpose Output

One machine, multiple uses



Extensive Applications



Oven and Electric Furnace



Environmental Protection



Laboratory Instruments




Light Industry Machinery

Standard Size

Match your hole-drilling requirements



More Product Information



■ Product Brand : **ENMG 恩霸**

■ Product Name : ETC5 PID Electronic Temperature Controller

■ Measurement Accuracy : $\pm 0.5\%FS$

■ Power Supply : 85~265VAC 50Hz

■ Resolution : 14 Bit

■ Sampling Period : 0.5 Secretary

■ Cold-Junction Compensation Error : $\pm 2^{\circ}C$ (Software correction is available within therange of)

■ Control Mode : Features expert self-tuning PID: rapid response, small overshoot, high precision

■ Insulation Resistance : $>50M\Omega$ (500VDC)

■ Dielectric Strength : 1500VAC/1min

■ Power Consumption : $<10VA$


■ Display Mode : Dual-row 4-digit display

■ Operating Environment : $0\sim 50^{\circ}C$, Occasions with noncorrosive gases and a relativehumidity of 30-85%RH

Specifications

Model Description

The design of product models and ordering codes aims to cover all possible specifications of this series of products, and they cannot be combined arbitrarily.If you have any questions during the first selection, please contact technical service engineers for confirmation.If the technical specifications in the product library fail to meet your needs, customization is available! Items marked with * are customized products.



① Product Name

Code	Explanation
ETC5	PID Electronic Temperature Controller

② Panel Size / Mounting Method

Code	Explanation
N	Panel Size: 48×24mm
S	Panel Size: 48×48mm Cutout Dimensions: 45×45mm
W	Panel Size: 96×48mm
H	Panel Size: 48×96mm Cutout Dimensions: 45×93mm
M	Panel Size: 72×72mm Cutout Dimensions: 69×69mm
L	Panel Size: 96×96mm Cutout Dimensions: 93×93mm
D	22.5mm Wide DIN Rail Mounting

③ Control Output

Code	Explanation
RX	Relay Output
QX	Voltage Output (Used to drive SSR)
CX	Linear Current Output (Such as 4-20mA)
QR	Voltage Output (Used to drive SSR) + Relay Output
RR	Dual Relay Output

④ Auxiliary Output

Code	Explanation
1	1 Auxiliary Contact
2	2 Auxiliary Contact

⑤ Power Supply Specifications

Code	Explanation
A	AC 85-240V (Wide-Range AC)
D	AC/DC 24V (Dual AC/DC Compatible)

⑥ Terminal Block Type

Code	Explanation
S	Screw Terminal
P	Spring Insert Terminal

⑦ Input Type

Code	Explanation
M	Full-Range Universal Input (Supports Multiple Signals)

Note: Input Range Table

	Input	Measurement Range	Code	Measurement Range	Code	Measurement Range	Code
Thermocouple	K	0~200°C	K01	0~400°C	K02	0~600°C	K03
		0~800°C	K04	0~1000°C	K05	0~1200°C	K06
		0~1372°C	K07	0~100°C	K13	0~300°C	K14
	J	0~200°C	J01	0~400°C	J02	0~600°C	J03
		0~800°C	J04	0~1000°C	J05	0~1200°C	J06
	R#1	0~1600°C	R01	0~1769°C	R02	0~1350°C	R04
	S#1	0~1600°C	S01	0~1769°C	S02		
	B#1	400~1800°C	B01	0~1769°C	B02		
	E	0~800°C	E01	0~1000°C	E02		
	N	0~1200°C	N01	0~1300°C	N02		
Thermal Resistance	T#2	-199.9~400.0°C	T01	-199.9~100.0°C	T02	-100~200.0°C	T03
		0~350°C	T04				
	Pt100	-199.9~649.0°C	D01	-199.9~200.0°C	D02	-100~50.0°C	D03
		-100~100°C	D04	-100~200.0°C	D05	0.0~50.0°C	D06
		0.0~100°C	D07	0.0~200.0°C	D08	0.0~300°C	D09
		0.0~500°C	D10				
	Cu50	-199.9~649.0°C	P01	-199.9~200.0°C	P02	-100~50.0°C	P03
		-100~100°C	P04	-100~200.0°C	P05	0.0~50.0°C	P06
		0.0~100°C	P07	0.0~200.0°C	P08	0.0~300°C	P09
		0.0~500°C	P10				
Standard Signal	0~5VDC	0.0~100°C	401				
	1~5VDC	0.0~100°C	601				
	0~20mA#3	0.0~100°C	701				
	4~20mA#3	0.0~100°C	801				


⑧ Communication Interface

Code	Explanation
R	RS-485 Modbus RTU

* Product features and appearance structure are subject to change due to technological innovation and improvement without prior notice;
Due to reasons such as shooting, typesetting, printing, etc., there will be slight differences between the product images and the actual products.


Overall and Mounting Hole Dimensions

ETC5S-QR1ASM




*Note: Unit: mm. The dimension data is measured manually, so deviations may exist. Please refer to the actual product.

ETC5M-QR1ASM




*Note: Unit: mm. The dimension data is measured manually, so deviations may exist. Please refer to the actual product.

ETC5H-QR1ASM



*Note: Unit: mm. The dimension data is measured manually, so deviations may exist. Please refer to the actual product.


ETC5L-QR1ASM




*Note: Unit: mm. The dimension data is measured manually, so deviations may exist. Please refer to the actual product.

Terminal Description

ETC5S




ETC5H, ETC5M, ETC5L




Wiring Application


Thermocouple Input




RTD Input




Alarm Output




Relay Output



Single-Phase Solid-State Output



Three-Phase Solid-State Output





Started in 2012, exploring the frontier, leading innovation, self-transformation, the world of ideas.

始于2012年，探索前沿、创新引领、自我蜕变、理念世界。

ENMG INTELLIGENT TECHNOLOGY

恩爵ENMG智能科技

Zhejiang ENMG Intelligent Technology Co., Ltd.

浙江恩爵智能科技有限公司

Wenzhou Yuanzhang Electric Co., Ltd.

温州元璋电气有限公司

公司地址 Address：浙江省乐清市柳市镇柳江路3788号


联系方式 Telephones：400-996-2708

官方网站 Website：www.enjue.cc

迪威模型 3D Model：www.3dwhere.com/user/135269



微信公众号
WeChat Public



微信客服
WeChat Clientele Services

入驻平台 ENTRY PLATFORM

在线搜索“恩爵旗舰店”，线上下单实惠方便！


Search for “ENMG Flagship Store” online, ordering online is affordable and convenient !



天猫 Tmall



淘宝 Taobao




1688



京东 JD



拼多多 PDD



抖音 TikTok



速卖通 AliExpress